





Quality Products. Service Excellence.

Tube Driver - Interstage 126 Series

Features



- Designed for driver use ONLY in single ended tube output amplifiers. These units replace coupling capacitor circuits for improved sound.
- Closed style with minimum 8" long leads.
- All models use bifilar wound windings for exceptional coupling and bandwidth.
- Minimum frequency response 20 Hz. - 20 KHz (+/- 1db max. ref. 1 KHz.).
- The core is gapped to support the specified D.C. bias current.
- Maximum working voltage - 400 VDC
- Units are Hi-Pot tested at 1,000 VDC
- Core uses Hi grade silicon laminations (29M6).
- Units weight - 3 lbs. 2 oz.



Part No.	Primary			Secondary				Dimensions							G Mtg Slot	
	Audio Watts	Impedance (Ohms)	Resistance (Ohms)	D.C.			Inductance	Rated D.C.	Bias Current	A	B	C	D	E		
				Impedance (Ohms)	Resistance (Ohms)	D.C.										
126A	4	5K	178	5K	178	59 Henrys	15 ma.	2.50	3.12	3.12	2.00	2.25	0.20	0.38		
126B	4	5K	178	5K	178	44 Henrys	30 ma.	2.50	3.12	3.12	2.00	2.25	0.20	0.38		
126C	4	10K	375	10K	375	106 Henrys	15 ma.	2.50	3.12	3.12	2.00	2.25	0.20	0.38		

Data subject to change without notice

© 2019. Hammond Manufacturing Ltd. All rights reserved.